



*Please specify the power supply type.

POWER SUPPLY	APPLICATION TYPE DESIGNATION
AC100V	PRL-6-WP
AC200V	PRL-6-VP

○ (Required power supply)

MICRO SWITCH
 250V AC 5A RESISTIVE LOAD
 COLOR: 10YR7.5/14
 DETECTION TORQUE: About 10.0N·cm
 REVOLUTION: 1RPM
 AMBIENT TEMPERATURE: -10~+40°C

*Please specify the length.

	l	l_0	NOTE	Q'ty
	450~600	0~150		
	650~1000	0~350		
	750~1200	0~450		

○ (Required length)

*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
GEUL10-G P1	$\phi 11 \sim \phi 12$
GEUL10-G P2	$\phi 10 \sim \phi 11$
GEUL10-G P3	$\phi 9 \sim \phi 10$
GEUL10-G P4	$\phi 8 \sim \phi 9$

○ (Required cable gland)

APPLICATION RANGE: Ex d IIB T4 Gb
 APPROVAL No.: TC22542X
 EXPLOSION-PROTECTED CONSTRUCTION: d
 EXPLOSION CLASS: IIB
 Temperature class: T4

Q'ty:

図章 CHANGE NOTICE 承認 APPROVED 検図 CHECKED 製図 DRAWN takahashi 日付 DATE Jan,21,2020	第三角法 THIRD ANGLE PROJECTION 尺度 SCALE 1:2	名称 TITLE PADDLE TYPE TPE-100EB LEVEL SWITCH 図面番号 DRG. No. HR-95013	東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.
--	--	--	--