



*Please specify the power supply type.

POWER SUPPLY	APPLICATION TYPE DESIGNATION
AC100V	PRL-6-WP
AC200V	PRL-6-VP

○(Required power supply)

MICRO SWITCH
250V AC 5A RESISTIVE LOAD
COLOR : 10YR7.5/14
DETECTION TORQUE : About 10.0N·cm
REVOLUTION : 1RPM
AMBIENT TEMPERATURE : -10~+40°C

*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
GEUL10-G P1	φ 11~ φ 12
GEUL10-G P2	φ 10~ φ 11
GEUL10-G P3	φ 9~ φ 10
GEUL10-G P4	φ 8~ φ 9

○(Required cable gland)

APPLICATION RANGE: Ex d IIB T4 Gb
APPROVAL No.: TC22542X
EXPLOSION-PROTECTED CONSTRUCTION: d
EXPLOSION CLASS: IIB
Temperature class: T4

Q'ty:

図番 CHANGE NOTICE	承認 APPROVED	検図 CHECKED	製図 DRAWN	名称 TITLE
			takahashi	PADDLE TYPE TPE-100F LEVEL SWITCH
	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2	日付 DATE Jan,21,2020	図面番号 DRG. No. HR-95015
東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.				