



*Please specify the power supply type.

POWER SUPPLY	APPLICATION TYPE DESIGNATION
AC100V	PRL-6-WP
AC200V	PRL-6-VP

○(Required power supply)

MICRO SWITCH
 250V AC 5A RESISTIVE LOAD
 COLOR: 10YR7.5/14
 DETECTION TORQUE: About 10.0N·cm
 REVOLUTION: 1RPM
 AMBIENT TEMPERATURE: -10~+40°C

*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
GEUL10-G P1	φ 11~φ 12
GEUL10-G P2	φ 10~φ 11
GEUL10-G P3	φ 9~φ 10
GEUL10-G P4	φ 8~φ 9

○(Required cable gland)

APPLICATION RANGE: Ex d IIB T4 Gb
 APPROVAL No.: TC2254-2X
 EXPLOSION-PROTECTED CONSTRUCTION: d
 EXPLOSION CLASS: IIB
 Temperature class: T4

Q'ty:

図番 CHANGE NOTICE 承認 APPROVED 検図 CHECKED 製図 DRAWN takahashi	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2	日付 DATE Jan,21,2020	Temperature in the tank : Max.200°C	名称 TITLE PADDLE TYPE LEVEL SWITCH
				東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.	図面番号 DRG. No. HR-95017