

*Please specify the power supply type.

POWER SUPPLY	APPLICATION TYPE DESIGNATION
AC100V	PRL-6-WP
AC200V	PRL-6-VP

○ (Required power supply)

MICRO SWITCH
250V AC 5A RESISTIVE LOAD
COLOR : 10YR7.5/14
DETECTION TORQUE : About 10.0N·cm
REVOLUTION : 1RPM
AMBIENT TEMPERATURE : -10~+40°C

*Please specify the length.

	ℓ	ℓ _o	NOTE	Q'ty
	470~620	0~150		
	670~1020	0~350		
	770~1220	0~450		


○ (Required length)

FLANGE	JISK 65A
MATERIAL	ALUMINUM CASTING
OUTSIDE DIAMETER	φ 155
DIAMETER OF BOLT CIRCLE	φ 130
DIAMETER OF BOLT HOLES	φ 15
NUMBER OF BOLT HOLES	4
THICKNESS	12

*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
GEUL10-G P1	φ 11~φ 12
GEUL10-G P2	φ 10~φ 11
GEUL10-G P3	φ 9~φ 10
GEUL10-G P4	φ 8~φ 9

○ (Required cable gland)

 APPLICATION RANGE: Ex d IIB T4 Gb
 APPROVAL No.: TC22542X
 EXPLOSION-PROTECTED CONSTRUCTION: d
 EXPLOSION CLASS: IIB
 Temperature class: T4

Q'ty:

図番 CHANGE NOTICE 承認 APPROVED 検図 CHECKED 製図 DRAWN takahashi	Temperature in the tank : Max.200°C		名称 TITLE PADDLE TYPE TPE-200FEB LEVEL SWITCH
	第三角法 THIRD ANGLE PROJECTION		図番番号 DRG. No. HR-95018
尺度 SCALE 1:2		日付 DATE Jan,21,2020	東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.