



*Please specify the power supply type.

POWER SUPPLY	APPLICATION TYPE DESIGNATION
AC100V	PRL-6-WP
AC200V	PRL-6-VP

○ (Required power supply)

MICRO SWITCH
250V AC 5A RESISTIVE LOAD
COLOR : 10YR7.5/14
DETECTION TORQUE : About 10.0N · cm
REVOLUTION : 1RPM
AMBIENT TEMPERATURE : -10 ~ +40°C

*Please specify the length.

	ℓ	ℓ _o	NOTE	Q'ty
	1020~1520	0~500		
	1220~2020	0~800		
	1520~2520	0~1000		
	1720~3020	0~1300		

○ (Required length)

FLANGE	JIS5K 65A
MATERIAL	ALUMINUM CASTING
OUTSIDE DIAMETER	φ 155
DIAMETER OF BOLT CIRCLE	φ 130
DIAMETER OF BOLT HOLES	φ 15
NUMBER OF BOLT HOLES	4
THICKNESS	12

*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
GEUL10-G P1	φ 11 ~ φ 12
GEUL10-G P2	φ 10 ~ φ 11
GEUL10-G P3	φ 9 ~ φ 10
GEUL10-G P4	φ 8 ~ φ 9

○ (Required cable gland)

APPRICATION RANGE: Ex d IIB T4 Gb
APPROVAL No. : TC22542X
EXPLOSION-PROTECTED CONSTRUCTION: d
EXPLOSION CLASS: IIB
Temperature class: T4

Q'ty :

図番 CHANGE NOTICE	承認 APPROVED	検図 CHECKED	製図 DRAWN	Temperature in the tank : Max.200°C	名称 TITLE
			takahashi		PADDLE TYPE TPE-200FED LEVEL SWITCH
	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2	日付 DATE Jan,21,2020	東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.	図面番号 DRG. No. HR-95019