



MOTOR  
W P 50/60Hz  
CONTINUOUS RATING  
INSULATION OF A KIND

MICRO SWITCH  
AC250V 5A  
RESISTIVE LOAD  
DC250V 0.3A  
RESISTIVE LOAD

POWER SUPPLY : AC V  
REVOLUTION : 1RPM  
TORQUE : about 9.8N·cm (about 1.0kg·cm)  
COLOR : 7.5BG4/1.5

	ℓ	NOTE	Q'ty
	1000		
	1500		
	2000		

ℓ (Required length)

THE STRUCTURAL THAT THE PART TAKING THE OUTERNAL LEADWIRES INTO THE TERMINAL BOX.



REFER TO THE "TECHNICAL RECOMMENDATIONS OF THE RESEARCH INSTITUTE OF INDUSTRIAL SAFETY" AND RECOMMENDED PRACTICE FOR ELECTRICAL EQUIPMENT FORUSE IN EXPLOSIVE EQUIPMENT" FOR THE WIRING IN THE TERMINAL BOX, TAKING THE OUTERNAL LEADWIRES INTO THE TERMINAL BOX, AND EARTH.

a reduced drawing (A3 size ~)

Q'ty:

図曆 CHANGE NOTICE	承認 APPROVED <i>Ym</i>	検図 CHECKED <i>K. Okamoto</i>	製図 DRAWN ohno	名称 TITLE PRL-G5-25 PADDLE TYPE LEVEL SWITCH
	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2.5	日付 DATE Feb,14,2008	図面番号 DRG. No. R-90972
			東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.	